

vidlicové šachtové stupadlo - jednořadý žebřík

Ocel s polyethylénovým povlakem - s jedním ohybem, krátká bočnice

Kód	SCSSO
Materiál	PE-HD, ocel
Hmotnost	1 kg
Norma	EN13101
Balení	800 ks/pal

Šachtové stupadlo typ "C"

OSTATNÍ:

- Dle EN13101.
- L = 295 mm; P = 152 mm; T = 25 mm; W = 37 mm; H = 35 mm
- Průměr stupadla 26mm
- Svislé zatížení – trvalá deformace ≤ 50 mm při svislém zatížení 4 kN

Warning: file_exists(): open_basedir restriction in effect.

File(/var/www/clients/client1/web105/web/media/product/image/4910.png) is not within the allowed path(s):

(/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-dev2.vicko.cz/web:/srv/www/kasi-

dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media) in /var/www/clients/client1/web105/web/app/model/product/ProductImageManager.php on line 272

Warning: file_exists(): open_basedir restriction in effect. File(/var/www/clients/client1/web105/web/media/product/technical/4910.png) is not within the allowed path(s): (/var/www/clients/client1/web105/web:/var/www/clients/client1/web105/private:/var/www/clients/client1/web105/tmp:/var/www/kasi-dev2.vicko.cz/web:/srv/www/kasi-

dev2.vicko.cz/web:/usr/share/php5:/usr/share/php:/tmp:/usr/share/phpmyadmin:/etc/phpmyadmin:/var/lib/phpmyadmin:/var/www/clients/client1/web98/web/media) in /var/www/clients/client1/web105/web/app/model/product/ProductImageManager.php on line 272

